

AGRIMAX PROHARVEST - Technical Specifications



Description

AGRIMAX PROHARVEST is BKT's response to the current market needs in terms of combines and harvesting machines. The advanced VF (Very High Flexion) technology allows AGRIMAX PROHARVEST to carry 40% more load compared to standard tires with the same tire pressure minimizing soil compaction. Moreover, the three layers of steel belts combined with the cut and chip resistant compound ensure excellent puncture resistance, even on case of stubbles or crops leftovers on the field. The structure of the tire with a reinforced bead and a strong polyester carcass is synonym of durability and stability of the tire even during heavy duty operation. The tire casing, engineered to guarantee high load capacity, combined with the CFO (Cyclic Field Operation) technology allows AGRIMAX PROHARVEST to handle temporary overloads during operations like harvesting, reducing stress and wear on the tire. Once the load is reduced, the tire returns to its standard operating condition, thus extending its service life and improving operational efficiency. The open shoulder design improves traction on rough and wet terrain while facilitating the ejection of mud and debris, ensuring smooth transitions from field to road and enhancing safety. On the field and on the road AGRIMAX PROHARVEST can reach up to 65km/h making your transit operation easier and faster thus improving overall productivity.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Harvester

Version

STEEL BELTED

Type

TL

Tyre Size	VF800/70 R 32 CFO
LI/SS	187 D
Dimensions International Standard	
Section Width (mm)	804
Overall Diameter (mm)	1933
Static Loaded Radius (mm)	846
Rolling Circumference (mm)	5817
SRI (mm)	925
Rim Rec	DW 28 B
ECE	E11-106R-0010664

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	4165	4785	5495	6205	6915	7625	8335	8870
from 65 to 40	4580	5265	6045	6825	7605	8385	9165	9750
30	4670	5370	6165	6960	7755	8550	9345	9945
20	4765	5475	6285	7095	7905	8720	9530	10140
10	5040	5790	6645	7505	8365	9220	10080	10725
Upto 30 Cyc	5200	5975	6860	7745	8630	9515	10400	11065
Upto 15 Cyc	6205	7130	8190	9245	10300	11360	12415	13210
Upto 10 Cyc	6800	7815	8970	10130	11290	12445	13605	14475
10HT	4670	5370	6165	6960	7755	8550	9345	9945

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 14/03/2025 14:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..