

AGRIMAX RT 855 - Technical Specifications



Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	210/95 R 18 (7.50 R 18)
LI/SS	108 A8/B

Dimensions US Standard

Usa code	94028672
Section Width (inch)	8.4
Overall Diameter (inch)	33.7
Static Loaded Radius (inch)	15.2
Rolling Circumference (inch)	101
Rim Rec	W 7
Rim Alt	W 6
ECE	E4-106R-00634
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
30	1040	1190	1370	1540	1720	1900	2050	2210
25	1040	1190	1370	1540	1720	1900	2050	2210
20	1110	1280	1470	1650	1840	2040	2200	2360
5 LT	1390	1600	1840	2070	2310	2550	2760	2950
5 HT	1110	1280	1470	1650	1840	2040	2200	2360

Printed on 25/07/2024 04:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..