

## AGRIMAX RT 855 - Technical Specifications



### Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	250/85 R 28 (9.5 R 28)
LI/SS	112 A8/B

## Dimensions US Standard

Usa code	94037520
Section Width (inch)	9.9
Overall Diameter (inch)	44.8
Static Loaded Radius (inch)	20.4
Rolling Circumference (inch)	134.7
Rim Rec	W 8
Rim Alt	W 7 ; W 9
ECE	E4-106R-000646
TRA Code	R1W

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23
30	1370	1590	1810	2030	2250	2470
25	1370	1590	1810	2030	2250	2470
20	1450	1700	1940	2170	2410	2650
5 LT	1830	2130	2420	2720	3020	3320
5 HT	1450	1700	1940	2170	2410	2650

Printed on 18/09/2024 12:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..