

AGRIMAX RT 855 - Technical Specifications



Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

UM

International Standard

Construction

RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Туре	TL
Tyre Size	320/85 R 24 (12.4 R 24)
LI/SS	122 A8/B

Dimensions International Standard

Section Width (mm)	329
Overall Diameter (mm)	1154
Static Loaded Radius (mm)	490
Rolling Circumference (mm)	3424
SRI (mm)	550
Rim Rec	W 11
Rim Alt	W 9 ; W 10
ECE	E4-106R-000613
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	825	960	1095	1230	1365	1500
40	825	960	1095	1230	1365	1500
30	885	1030	1175	1320	1465	1605
10 LT	1110	1290	1470	1650	1830	2010
10 HT	885	1030	1175	1320	1465	1605

Printed on 20/07/2024 18:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..