

# **AGRIMAX RT 855 - Technical Specifications**



## **Description**

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

#### UM

**US Standard** 

#### Construction



## Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Туре	TL
Tyre Size	420/80 R 46 (16.9 R 46)
LI/SS	151 D/162 A2

## **Dimensions US Standard**

Usa code	94046089
Section Width (inch)	16.5
Overall Diameter (inch)	72.4
Static Loaded Radius (inch)	34
Rolling Circumference (inch)	222.1
Rim Rec	W 13
Rim Alt	W 12
ECE	E4-106R-001730
TRA Code	R1W

# Load capacity (lbs)

<b>40</b> 3580 4110 4720 5320 5940 6550 7080 7610	mph / psi
	40
<b>30</b> 3760 4320 4960 5600 6240 6880 7440 7990	30
<b>25</b> 3920 4510 5170 5840 6500 7180 7760 8330	25
<b>20</b> 4120 4730 5430 6130 6830 7530 8150 8750	20
<b>5</b> 4930 5650 6490 7330 8170 9010 9740 10470	5
<b>5LT</b> 4790 5510 6330 7140 7960 8770 9490 10200	5 LT
<b>5 HT</b> 4120 4730 5430 6130 6830 7530 8150 8750	5 HT

#### Printed on 25/07/2024 04:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..