

## AGRIMAX RT 955 - Technical Specifications



### Description

AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying and vineyards. The special tread design with a rounded shoulder provides excellent traction performance, stability and self-cleaning properties. Thanks to its strong casing, AGRIMAX RT 955 has a high load capacity.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Sprayer • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	210/90 R 24 (8.3 R 24)
LI/SS	107 A8/B

## Dimensions US Standard

Usa code	94042531
Section Width (inch)	8.4
Overall Diameter (inch)	39.8
Static Loaded Radius (inch)	18.2
Rolling Circumference (inch)	119.2
Rim Rec	W 7
Rim Alt	W 6
ECE	E4-106R-001818
TRA Code	R1

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35	41
30	1010	1170	1330	1510	1690	1850	2010	2150	-
25	1010	1170	1330	1510	1690	1850	2010	2150	-
20	1090	1250	1430	1620	1810	1980	2150	2300	-
5	1490	1720	1910	2110	2330	2560	2980	3140	3230

Printed on 30/06/2024 20:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..