

AGRIMAX RT 955 - Technical Specifications



Description

AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying and vineyards. The special tread design with a rounded shoulder provides excellent traction performance, stability and self-cleaning properties. Thanks to its strong casing, AGRIMAX RT 955 has a high load capacity.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	210/95 R 32 (8.3 R 32)
LI/SS	120 A8/B

Dimensions International Standard

Section Width (mm)	214
Overall Diameter (mm)	1213
Static Loaded Radius (mm)	571
Rolling Circumference (mm)	3703
SRI (mm)	575
Rim Rec	W 7
Rim Alt	W 6
ECE	E4-106R-001391
TRA Code	R1

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6
50	645	830	1010	1095	1190	1305	1400	-
40	645	830	1010	1095	1190	1305	1400	-
30	690	885	1080	1170	1275	1395	1500	-
10	905	1180	1430	1555	1660	1830	1975	2100

Printed on 06/07/2024 20:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..