

## AGRIMAX RT 955 - Technical Specifications



### Description

AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying and vineyards. The special tread design with a rounded shoulder provides excellent traction performance, stability and self-cleaning properties. Thanks to its strong casing, AGRIMAX RT 955 has a high load capacity.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agriculture: Sprayer • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	340/85 R 48 (13.6 R 48)
LI/SS	152 A8/B

## Dimensions International Standard

Section Width (mm)	353
Overall Diameter (mm)	1797
Static Loaded Radius (mm)	855
Rolling Circumference (mm)	5572
SRI (mm)	875
Rim Rec	W 12
Rim Alt	W 11
ECE	E4-106R-000800
TRA Code	R1

## Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
50	1385	1815	2205	2415	2560	2805	3055	3305	3550	-
40	1385	1815	2205	2415	2560	2805	3055	3305	3550	-
30	1485	1940	2360	2585	2740	3005	3270	3535	3800	-
10	1655	2080	2560	3040	3515	3625	4050	4475	4900	5325

Printed on 06/07/2024 20:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..