

AGRIMAX TURF RT 333 - Technical Specifications



Description

AGRIMAX TURF RT 333 (R-3+) is a radial tire designed for small tractors in gardening, vineyards and orchards applications. Its rounded shoulder design provides low soil compaction and makes it extremely delicate on the ground. Its unique extra-deep tread (R-3+) and the special design with directional blocks stand for excellent traction both in the field and on the road, and an extended tire life cycle. AGRIMAX TURF RT 333 (R-3+) ensures great self-cleaning properties and thanks to its low rolling resistance, allows for significant fuel saving.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Orchard Harvester • Small Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	320/65 R 18
LI/SS	109 A8/109 B

Dimensions US Standard

Usa code	94071081
Section Width (inch)	12.6
Overall Diameter (inch)	34.4
Static Loaded Radius (inch)	15.5
Rolling Circumference (inch)	102
Rim Rec	W 10
Rim Alt	W 9 ; W 11
ECE	E11-106R-007844

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
30	1260	1460	1670	1870	2080	2280
25	1260	1460	1670	1870	2080	2280
20	1350	1570	1790	2010	2230	2440
5 LT	1690	1970	2240	2520	2790	3060
5 HT	1350	1570	1790	2010	2230	2440

Printed on 30/06/2024 17:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..