

AGRIMAX V-FLECTO - Technical Specifications



Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the exclusive VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: High-Power Tractor

Version	STANDARD
Type	TL
Tyre Size	VF 600/60 R 38 NRO
LI/SS	168 D

Dimensions US Standard

Usa code	94065356
Section Width (inch)	23.1
Overall Diameter (inch)	66.3
Static Loaded Radius (inch)	29.8
Rolling Circumference (inch)	199.9
Rim Rec	DW 20 B
Rim Alt	DW 18 L
Narrow Rim option	DW 18 L
ECE	E11-106R-006414
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
45	5170	5960	6860	7640	8540	9330	10450	11230
From 40 to 25	5690	6550	7540	8400	9390	10250	11490	12350
20	5800	6680	7680	8560	9570	10450	11720	12590
12	5910	6800	7840	8730	9750	10660	11940	12830
5	6250	7200	8290	9240	10330	11280	12630	13580
*Upto 5 Cyc with front loader	7960	9170	10550	11760	13140	14350	16080	17280
5 HT	5800	6680	7680	8560	9570	10450	11720	12590

* *For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Printed on 17/07/2024 23:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..