

AS 504 - Technical Specifications



Description

AS 504 is an agro-industrial tire mainly designed for soil tillage, implement and material-handling operations. This tire, which features excellent self-cleaning properties and increased grip, is suitable for field trailers and telehandlers. AS 504 is available in several versions to meet specific end-user requirements: an "HD" version with a special cut-and-chip resistance compound, while the "special" version has a reinforced casing that ensures a longer tire life.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Telehandler • Field Trailer

Industrial: Telehandler

Version	STANDARD
Type	TT
Tyre Size	27 X 10 - 15.3
LI/SS DRIVE WHEEL	95 A8
LI/SS FREE ROLLING	107 A8

Dimensions International Standard

Ply Rating	8
Section Width (mm)	260
Overall Diameter (mm)	695
Static Loaded Radius (mm)	317
Rolling Circumference (mm)	2071
Rim Rec	9.00
ECE	E4-106R-002324

Load capacity (Kg)

	km/h / bar	3.10
	10 FR	1365
	25 FR	1160
	30 FR	1090
	40 FR	975
	10 DW	965
	25 DW	820
	30 DW	775
	40 DW	690

Printed on 20/07/2024 18:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..