

AT 110 - Technical Specifications



Description

AT 110 is BKT's tire suitable for all-terrain applications with ATVs. Thanks to its extraordinary steering control, AT 110 is the ideal front axle tire for your vehicle.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: ATV

| | |
|-----------|---------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | AT 21 X 8 - 9 |

Dimensions US Standard

| | |
|-------------------------|----------|
| Usa code | 94000791 |
| Ply Rating | 4 |
| Section Width (inch) | 8 |
| Overall Diameter (inch) | 21.3 |
| Rim Rec | 6.5 AT |
| Rim Alt | 6.0 AT |

Load capacity (lbs)

| mph / psi | 5 |
|-----------|-----|
| 50 | 225 |

Printed on 20/07/2024 18:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..