

## AW 702 IND - Technical Specifications



### Description

AW 702 IND has been developed for Industrial trailers applications. This heavy-duty tire has been designed by BKT to provide a new level of durability.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrial: Trailer

Version	INDUSTRIAL
Type	TT
Tyre Size	6.00 - 16
LI/SS FREE ROLLING	103 A8

## Dimensions International Standard

Ply Rating	8
Section Width (mm)	169
Overall Diameter (mm)	722
Static Loaded Radius (mm)	337
Rolling Circumference (mm)	2150
Rim Rec	4.00 E
Rim Alt	4.50 E ; 4½ K
ECE	E11-106R-004358

## Load capacity (Kg)

	km/h / bar	4.00
	10 FR	1225
	25 FR	1040
	30 FR	980
	40 FR	875

Printed on 01/07/2024 06:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..