

BK-LOADER 53 - Technical Specifications



Description

BK-LOADER 53 is an aramid-belted tire designed for loaders in industrial applications. The unique tread design provides best lateral stability in addition to extended tread wear and extraordinary resistance against cuts and punctures thanks to the extra deep tread. BK-LOADER 53 features outstanding self-cleaning properties as well as excellent grip and traction on both wet and dry surfaces. This tire is particularly suitable for recycling operations.

UM

US Standard

Construction

 RADIAL

Machinery

Industrial: Loader

Version	ARAMID BELTED
Type	TL
Tyre Size	365/70 R 18
LI/SS	146A2/142A4

Dimensions US Standard

Usa code	94074143
Section Width (inch)	14.2
Overall Diameter (inch)	39
Static Loaded Radius (inch)	18
Rolling Circumference (inch)	118.8
Rim Rec	11

Load capacity (lbs)

mph / psi	22	29	36	44	51	58	65	73	80
12	2060	2640	3100	3580	4090	4510	4980	5380	5850
5	2320	2980	3510	4040	4630	5100	5630	6090	6620
STATIC	3690	4740	5580	6420	7370	8110	8940	9680	10520

Printed on 30/06/2024 18:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..