

EARTHMAX SR 49 M - Data Sheet



Description

EARTHMAX SR 49 M is an All Steel radial tire with a special non-directional pattern designed for load haul dumps (LHD), low profile dump trucks (LPDT), loaders and dozers operating in severe rocky conditions primarily in underground mining. EARTHMAX SR 49 M is ideal for severe operations requiring exceptional traction and stability. The L-4 deep tread and the specially formulated UMS (underground mine service) compound provide a longer tread wear in addition to excellent resistance to rock cuts, and punctures.

UM

International Standard

Construction

🗱 RADIAL

Machinery

OTR: Dozer • Load Haul Dump (LHD) • Loader • Low Profile Dump Truck (LPDT)

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	ow	OD	SLR	RC	Туре	ТКРН
26.5 R 25	CUT RESISTANT COMPOUND	L4	* *	209 A2	22.00/3.0		708	1782	801	5297	TL	
26.5 R 25	CUT RESISTANT COMPOUND	E4/L4	**/*	193 B/202 A2	22.00/3.0		708	1782	801	5297	TL	165
26.5 R 25	CUT RESISTANT COMPOUND	L4	*	202 A2	22.00/3.0		708	1782	801	5297	TL	
26.5 R 25	CUT RESISTANT COMPOUND	E4/L4	***/***		22.00/3.0		708	1782	801	5297	TL	
26.5 R 25	CUT RESISTANT COMPOUND (UMS)	E4	* * * *		22.00/3.0		708	1782	801	5297	TL	
29.5 R 25	CUT RESISTANT COMPOUND	L4	*	208 A2	25.00/3.5		780	1905	844	5600	TL	
29.5 R 25	CUT RESISTANT COMPOUND	L4	* *	216 A2	25.00/3.5		780	1905	844	5600	TL	
29.5 R 25	CUT RESISTANT COMPOUND	E4/L4	**/*	200 B/208 A2	25.00/3.5		780	1905	844	5600	TL	220
29.5 R 25	CUT RESISTANT COMPOUND	E4/L4	***/***		25.00/3.5		780	1905	844	5600	TL	
29.5 R 25	CUT RESISTANT COMPOUND (UMS)	E4	****		25.00/3.5		780	1905	844	5600	TL	
29.5 R 29	CUT RESISTANT COMPOUND	L4	* * *	223 A2	25.00/3.5	24.00/3.5,26.00/3.5	786	2006	906	6320	ΤL	
29.5 R 29	CUT RESISTANT COMPOUND (UMS)	E4	****		25.00/3.5	24.00/3.5, 26.00/3.5	786	2006	906	6320	ΤL	

Printed on 30/06/2024 17:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..