

FARM 2000 - Technical Specifications



Description

The FARM 2000 tire is suitable on tractors for soil tillage applications. It has been designed with a special cut-and-chip resistant compound to ensure better durability. Thanks to its strong casing, FARM 2000 offers high load capacity. It also provides great traction and self-cleaning properties.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	260/70 - 15.3
LI/SS DRIVE WHEEL	114 A8
LI/SS FREE ROLLING	126 A8

Dimensions US Standard

Usa code	94035366
Section Width (inch)	10.4
Overall Diameter (inch)	30.5
Static Loaded Radius (inch)	13.7
Rolling Circumference (inch)	90.3
Rim Rec	9.00
ECE	E11-106R-003516

Load capacity (lbs)

mph / psi	52
5 FR	5250
15 FR	4460
20 FR	4200
25 FR	3750
5 DW	3640
15 DW	3100
20 DW	2910
25 DW	2600

Printed on 25/07/2024 04:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..