

FARM 2000 - Technical Specifications



Description

The FARM 2000 tire is suitable on tractors for soil tillage applications. It has been designed with a special cut-and-chip resistant compound to ensure better durability. Thanks to its strong casing, FARM 2000 offers high load capacity. It also provides great traction and self-cleaning properties.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	300/80 - 15.3
LI/SS DRIVE WHEEL	120 A8
LI/SS FREE ROLLING	132 A8

Dimensions International Standard

Section Width (mm)	300
Overall Diameter (mm)	890
Static Loaded Radius (mm)	388
Rolling Circumference (mm)	2608
SRI (mm)	410
Rim Rec	9.00
ECE	E11-106R-003517

Load capacity (Kg)

	km/h / bar	2.80
	10 FR	2800
	25 FR	2380
	30 FR	2240
	40 FR	2000
	10 DW	1960
	25 DW	1665
	30 DW	1570
	40 DW	1400

Printed on 18/09/2024 12:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..