

FL 630 ULTRA - Technical Specifications



Description

FL 630 ULTRA is suitable for trailers, tankers and spreaders. Thanks to its reinforced bead and the particular tread design, it is the ideal tire for multipurpose use on any kind of land or on the road. FL 630 ULTRA stands for extraordinarily reduced soil compaction.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Spreader • Tanker • Trailer

Version	STANDARD
Type	TL
Tyre Size	650/55 R 26.5
LI/SS	169 D/180 A8

Dimensions International Standard

Section Width (mm)	645
Overall Diameter (mm)	1389
Static Loaded Radius (mm)	600
Rolling Circumference (mm)	4207
SRI (mm)	650
Rim Rec	AG 20.00
ECE	E11-106R-006814

Load capacity (Kg)

km/h / bar	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
65	1860	2150	2440	2960	3425	3945	4470	4815	5340	5800
50	2250	2600	2950	3585	4145	4775	5410	5830	6460	7020
40	2560	2960	3360	4080	4720	5440	6160	6640	7360	8000
25	2935	3395	3850	4675	5410	6235	7060	7610	8435	9165
10	3345	3865	4385	5325	6160	7100	8040	8670	9605	10440

Printed on 30/06/2024 17:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..