

FL 634 PERFORMA - Technical Specifications



Description

The new FL 634 PERFORMA is an All Steel radial tire that meets the growing demand for logistics in agriculture. Specifically designed for vehicles such as agro trucks and tank trucks, this tire embodies great efficiency and versatility making it suitable for transport operations from the harvest field to the processing or any other farm area. Engineered for high-speed performance, it ensures excellent roadability on asphalt along with smooth and rapid transportation, an essential need in modern agriculture. The innovative open shoulder and tread design significantly enhance tire traction both on the road and in the fields providing outstanding self-cleaning properties. The tread compound, the specific construction features, and a strong steel body ply with four steel belts make FL 634 PERFORMA synonym for robustness and resistance to any kind of damage ensuring a long service life. In addition, the bead has been reinforced with a steel chafer that ensures high clamping stability in any operation mode.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Agro Truck

Version	STANDARD
Type	TL
Tyre Size	600/50 R 22.5
LI/SS	164 J

Dimensions International Standard

Overall Width (mm)	615
Overall Diameter (mm)	1170
Static Loaded Radius (mm)	535
Rolling Circumference (mm)	3567
Rim Rec	AG 20.00
ECE	E11-54R-0020871

Load capacity (Kg)

km/h / bar	6.50
40	5750
100	5000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 10:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..