

FLOTATION 647 - Technical Specifications



Description

FLOTATION 647 is an implement tire that features best traction on soft soil and grassland. In addition to excellent self-cleaning properties, the specially designed tread pattern provides a wide contact area, which ensures optimized ground pressure and excellent performance on soft soil.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Implement Machinery

Version	STANDARD
Type	TL
Tyre Size	425/70 - 18
LI/SS DRIVE WHEEL	143 B
LI/SS FREE ROLLING	155 B

Dimensions US Standard

Usa code	94064373
Section Width (inch)	17.1
Overall Diameter (inch)	41.9
Rim Rec	13.00
ECE	E11-106R-005851

Load capacity (lbs)

mph / psi	51
30 FR	8550
30 DW	6000

Printed on 22/07/2024 11:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..