

FS 216 - Technical Specifications



Description

FS 216 has a robust log design with optimum angle and wider width to enhance traction performance for loggers and skidders. It provides excellent cut and chip resistance under the most critical operating conditions and ensures maximum protection against possible damages at any time.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Log Skidder

Version	STEEL BELTED
Type	TL
Tyre Size	30.5L - 32

Dimensions International Standard

Ply Rating	20
Section Width (mm)	775
Overall Diameter (mm)	1847
Static Loaded Radius (mm)	833
Rolling Circumference (mm)	5466
Rim Rec	DH 27
Rim Alt	DH 27 B
ECE	E11-106R-003439
TRA Code	LS2

Load capacity (Kg)

km/h / bar	2.40	2.10
10	8400	-
30	-	6000

Printed on 01/07/2024 05:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..