



## GRIP STAR - Data Sheet



### Description

GRIP STAR is an agro-industrial tire for loading applications with telehandlers. It shows excellent traction and self-cleaning properties. Besides, it is an all-season tire particularly suitable for operations on muddy ground. GRIP STAR is also available in a "special" version that features extra cut and chip resistance.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industrial: Telehandler

SIZE	Version	USACode	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type
15.5/80 - 24	SPECIAL	94035977	151 A6	163 A6	16	W 12	W 13 ; W 14 L	15.4	50	22.4	145	TL
15.5/80 - 24	STANDARD	94019762	151 A6	163 A6	16	W 12	W 13 ; W 14 L	15.4	50	22.4	145	TL
15.5/80 - 24	STANDARD	94048823	151 A6	163 A6	16	W 12	W 13 ; W 14 L	15.4	50	22.4	145	TT

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/09/2024 01:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..