

LG 307 - Technical Specifications



Description

LG 307 is a lawn and garden tire suitable for mowers. The specific tread pattern makes the tire gentle on the ground to prevent turf damages, easing handling at the same time.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Mower

Version	STANDARD
Type	TL
Tyre Size	20 X 10.00 - 8

Dimensions International Standard

Ply Rating	4
Section Width (mm)	255
Overall Diameter (mm)	495
Static Loaded Radius (mm)	215
Rolling Circumference (mm)	1435
Rim Rec	8.00 I - 55 ; I - 70 ; I - 90
Rim Alt	7.00 I - 55 ; I - 70 ; I - 90
ECE	E11-106R-005200

Load capacity (Kg)

km/h / bar	1.50
15	545

Printed on 01/07/2024 05:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..