

## LG RIB - Technical Specifications



### Description

LG RIB is a lawn and garden tire suitable for mowers and small tractors. Its tread pattern has been designed for making the tire gentle on the ground to prevent turf damages making handling easier at the same time. LG RIB is available in an "aramid-belted" version for users who need strengthened puncture resistance.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Mower • Small Tractor

Version	STANDARD
Type	TL
Tyre Size	13 X 5.00 - 6

## Dimensions International Standard

Ply Rating	4
Section Width (mm)	127
Overall Diameter (mm)	325
Static Loaded Radius (mm)	144
Rolling Circumference (mm)	943
Rim Rec	3.50 A
ECE	E11-106R-003465

## Load capacity (Kg)

km/h / bar	2.80
15	200

Printed on 20/07/2024 18:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..