



## LIFTMAX LM 63 - Data Sheet

### Description

LIFTMAX LM 63 has been specially developed for industrial and logistics operations. The 3-rib tread design provides low rolling resistance with good wet grip and uniform tread wear with better handling. It is an All Steel radial tire with multilayer steel belts offering lower vibration as well as enhanced stability and comfort



### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Hay Harvester

Industrial: Tow Tractor • Trailer

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	OW	OD	Type	ECE
<b>180/70 R 8 (18X7 R 8)</b>	STANDARD	94067008	125 A5	4.33R		6.7	18.1	TL	
<b>180/70 R 8 IMP (18X7 R 8)</b>	STANDARD	94067602	120 A8	4.33R		6.7	18.1	TL	E11-106R-006845
<b>6.00 R 9</b>	STANDARD	94063901	121 A5	4.00E		6.3	21.3	TL	
<b>6.50 R 10</b>	STANDARD	94066247	128 A5	5.00F	5.50 F	6.9	23.3	TL	
<b>7.00 R 12</b>	STANDARD	94066209	136 A5	5.00S		7.7	26.6	TL	
<b>7.00 R 15</b>	STANDARD	94066834	143 A5	5.50	5.00	7.8	29.1	TL	
<b>8.25 R 15</b>	STANDARD	94063635	153 A5	6.5	7.0	9.4	33.2	TL	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/09/2024 01:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..