

# LT TR 182 - Technical Specifications



## Description

LT TR 182 is suitable for transport operations on light trucks. This high-speed tire is road oriented and significantly reduces fuel consumption. The LT TR 182 tire is also easy to mount.

#### UM

International Standard

### Construction

BIAS

Machinery Industrial: Light Truck

VersionSTANDARDTypeTLTyre Size8 - 14.5

## **Dimensions International Standard**

| Ply Rating            | 14      |
|-----------------------|---------|
| Section Width (mm)    | 207     |
| Overall Diameter (mm) | 710     |
| Rim Rec               | 6.00 MH |

# Load capacity (Kg)

| km/h / bar | 7.90 |
|------------|------|
| 100 LS     | 1375 |
| 100 LD     | 1210 |

#### Printed on 19/07/2024 03:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..