

# **MAGLIFT ECO RIB - Technical Specifications**



**Tyre Size** 

### **Description**

MAGLIFT ECO RIB is a solid tire specially designed for GSE trailers (ground support equipment). Its reinforced structure eliminates slippage risks whilst the specifically designed rim guard ensures protection against wheel damage. MAGLIFT ECO RIB shows excellent steering control, high stability, low vibration and self-ment for trailers. Additional features are low rolling resistance and low heat built up for improved efficiency.

#### UM

International Standard

#### Construction

♦ SOLID

# Machinery

Industrial: Forklift

Version	TANDARD
Туре	

4.00 - 8

# **Dimensions International Standard**

Section Width (mm)	124
Overall Diameter (mm)	408
Rim Rec	3.75 I - 8

# Load capacity (Kg)

km/n / bar	<del>-</del>
5 OTHER VEHICLES	1010
10 OTHER VEHICLES	915
25 OTHER VEHICLES	775

#### Printed on 18/09/2024 12:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..