

# **MULTIMAX MP 513 - Technical Specifications**



## **Description**

MULTIMAX MP 513 has been designed by BKT for multipurpose vehicles in municipality/maintenance and transport applications, for both agricultural and industrial uses. It is perfect for universal vehicles and fertilizer trucks. Thanks to the strong steel-belted nylon casing, MULTIMAX MP 513 allows to carry heavy loads at high speeds providing a comfortable driving experience. It ensures a longer service life and traction along with outstanding selfcleaning properties.

#### **UM**

International Standard

#### Construction



#### **Machinery**

Agriculture: Universal Vehicle • Fertilizer Truck

Industrial: Universal Vehicle

Version	STANDARD
Туре	TL
Tyre Size	425/55 R 17 MPT
LI/SS	142 A8/B

## **Dimensions International Standard**

Section Width (mm)	421
Overall Diameter (mm)	900
Static Loaded Radius (mm)	399
Rolling Circumference (mm)	2705
Rim Rec	13
Rim Alt	13.00
ECE	E11-106R-006433

# Load capacity (Kg)

km/h / bar	1.2	1.6	2.0	2.4	2.8	3.2	3.5	4.0
50	1035	1275	1515	1725	1965	2200	2440	2650
40	1035	1275	1515	1725	1965	2200	2440	2650
30	1110	1365	1620	1850	2105	2360	2530	2840
25	1150	1415	1680	1915	2180	2445	2625	2945

#### Printed on 30/06/2024 20:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..