

MULTIMAX MP 540 - Technical Specifications



Description

MULTIMAX MP 540 has been designed by BKT for all multi-purpose vehicles. Thanks to the All Steel casing, MULTIMAX MP 540 enables to carry heavy loads during on and off road applications. In addition, its block pattern design provides outstanding stability and durability

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Universal Vehicle

Industrial: Universal Vehicle

Version	STANDARD
Type	TL
Tyre Size	335/80 R 20
LI/SS	149 K

Dimensions US Standard

Usa code	94033539
Overall Width (inch)	13.4
Overall Diameter (inch)	41.1
Static Loaded Radius (inch)	19.4
Rolling Circumference (inch)	128.3
Rim Rec	11
Rim Alt	-
ECE	E11-54R-0015909

Load capacity (lbs)

mph / psi	58	65	73	80	87	94
68	4860	5335	5810	6270	6725	7165
60	4860	5335	5810	6270	6725	7165
55	4960	5445	5920	6395	6855	7310
50	5050	5555	6040	6515	6990	7450
45	5205	5720	6215	6715	7200	7670

Printed on 30/06/2024 20:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..