

PAC MASTER - Technical Specifications



Description

PAC MASTER is a bias tire for compactors. It shows high stability and ensures an extended tire life-cycle. It is made of a special compound that provides particular heat resistance.

UM

International Standard

Construction



Machinery

Industrial: Compactor

Version	STANDARD
Туре	TL
Tyre Size	10.5/80 - 16

Dimensions International Standard

Ply Rating	14
Section Width (mm)	275
Overall Diameter (mm)	810
Static Loaded Radius (mm)	382
Rolling Circumference (mm)	2480
Rim Rec	8.0
ECE	E11-106R-004647

Load capacity (Kg)

km/h / bar	6.00
10	2775
15	2250

Printed on 19/07/2024 03:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..