

## RIB 900 - Technical Specifications



### Description

RIB 900 is suitable for transport, soil tillage and hay harvesting operations with trailers, implement machinery and balers. It offers great load capacity and a long tire life-cycle.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Baler • Hay Harvester • Implement Machinery  
• Trailer

Version	STANDARD
Type	TL
Tyre Size	400/60 - 15.5
LI/SS FREE ROLLING	147 A8

## Dimensions International Standard

<b>Ply Rating</b>	16
<b>Section Width (mm)</b>	405
<b>Overall Diameter (mm)</b>	875
<b>Static Loaded Radius (mm)</b>	380
<b>Rolling Circumference (mm)</b>	2564
<b>Rim Rec</b>	AG 13.00
<b>ECE</b>	E4-106R-001548

## Load capacity (Kg)

	km/h / bar	4.00
	10 FR	4305
	25 FR	3660
	30 FR	3445
	40 FR	3075

Printed on 19/07/2024 03:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..