

# **RIDEMAX FL 693 M - Technical Specifications**



## **Description**

RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks.

Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption, while a reinforced bead and steel belts ensure enhanced durability.

#### **UM**

**US Standard** 

#### Construction



## Machinery

Agriculture: Tanker • Trailer

Version	STANDARD
Туре	TL
Tyre Size	600/60 R 30.5
LI/SS	173 D

## **Dimensions US Standard**

Usa code	94069330
Section Width (inch)	23.8
Overall Diameter (inch)	58.9
Static Loaded Radius (inch)	26.8
Rolling Circumference (inch)	177
Rim Rec	AG 20.00
Rim Alt	AG 18.00
ECE	E11-106R-007198

## Load capacity (lbs)

mph / psi	15	17	23	29	35	41	46	52	58	65	73
45	4510	4960	6010	6660	7690	8740	9660	10570	11610	12390	13040
40	4950	5450	6590	7310	8450	9600	10600	11610	12750	13610	14330
30	5990	6590	7980	8850	10240	11620	12840	14050	15430	16480	17340
25	6720	7410	8970	9940	11510	13060	14430	15800	17350	18520	19490
20	7470	8220	9950	11040	12780	14510	16020	17540	19270	20560	21640
15	7810	8610	10420	11550	13360	15180	16750	18340	20160	21520	22640
5	8910	9810	11870	13160	15220	17280	19090	20900	22960	24500	25790

#### Printed on 30/06/2024 18:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..