

## RIDEMAX IT 696 - Technical Specifications



### Description

RIDEMAX IT 696 has a unique tread design and a wide footprint that provides excellent grip for road applications, even in winter conditions. The tire is best suitable for transport and municipality/maintenance applications thanks to its high-speed feature and strong casing. The tread design has been specifically developed for heavy-duty services and ensures a low rolling resistance that provides fuel economy plus great stability.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	480/80 R 30 IND (18.4 R 30)
LI/SS	162 A8/157 D

## Dimensions International Standard

Section Width (mm)	479
Overall Diameter (mm)	1530
Static Loaded Radius (mm)	673
Rolling Circumference (mm)	4558
SRI (mm)	725
Rim Rec	W 15 L
Rim Alt	W 16 L
ECE	E4-106R-002298

## Load capacity (Kg)

km/h / bar	1.2	1.6	2.0	2.4	2.8	3.2
65	1940	2395	2805	3260	3670	4125
50	2105	2600	3045	3540	3985	4480
40	2235	2755	3230	3755	4230	4750
30	2320	2865	3360	3905	4395	4940

Printed on 30/06/2024 20:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..