

SIERRA MAX - Technical Specifications



Description

SIERRA MAX is the BKT tire for both all-terrain and lawn and garden applications. Its radial construction provides a significantly smoother and more comfortable ride over extreme terrains such as deserts, or dirty and rocky surfaces. The special tread design along with its wider footprint provides outstanding forward and lateral traction.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: ATV

Version	STANDARD
Type	TL
Tyre Size	AT 27 X 9 R 14
LI/SS	50 N

Dimensions International Standard

Section Width (mm)	230
Overall Diameter (mm)	700
Static Loaded Radius (mm)	316
Rolling Circumference (mm)	2070
Rim Rec	7.00
Star Rating	***
ECE	E11-75R-005099

Load capacity (Kg)

km/h / bar	0.50
140	190

Printed on 19/07/2024 06:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..