

SL 441 - Technical Specifications

Description

SL 441 is a tire developed for soil tillage and haulage operations with trailers and implement machinery. SL 441 has been engineered to offer great load capacity and a long tire life-cycle.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Implement Machinery • Trailer



| | |
|--------------------|---------------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 200/60 - 14.5 |
| LI/SS FREE ROLLING | 106 A8 |

Dimensions US Standard

| | |
|------------------------------|----------|
| Usa code | 94011087 |
| Ply Rating | 10 |
| Section Width (inch) | 8.3 |
| Overall Diameter (inch) | 24 |
| Static Loaded Radius (inch) | 10.9 |
| Rolling Circumference (inch) | 70.3 |
| Rim Rec | AG 6.75 |

Load capacity (lbs)

| mph / psi | 73 |
|-----------|------|
| 5 FR | 2930 |
| 15 FR | 2490 |
| 20 FR | 2350 |
| 25 FR | 2090 |

Printed on 19/07/2024 03:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..