



SL 441 - Data Sheet

Description

SL 441 is a tire developed for soil tillage and haulage operations with trailers and implement machinery. SL 441 has been engineered to offer great load capacity and a long tire life-cycle.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Implement Machinery • Trailer



SIZE	Version	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
200/60 - 14.5	STANDARD	106 A8	10	AG 6.75		210	610	278	1785	TT	
200/60 - 14.5	STANDARD	113 A8	14	AG 6.75		210	610	278	1785	TL	E11-106R-003610
200/60 - 14.5	STANDARD	113 A8	14	AG 6.75		210	610	278	1785	TT	E11-106R-003610

Printed on 19/07/2024 03:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..