

## SNOW - RIDE (A) - Technical Specifications



### Description

SNOW-RIDE is particularly suitable for municipality and maintenance applications in winter conditions with compact loaders and skid steers. It features excellent traction and is ideal for ice and snow operations. Its specially designed tread pattern eliminates slippage risks and ensures a longer tire life-cycle.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Compact Loader  
Industrial: Skid Steer

|           |              |
|-----------|--------------|
| Version   | STANDARD     |
| Type      | TL           |
| Tyre Size | 12.5/70 - 16 |

## Dimensions International Standard

|                                   |       |
|-----------------------------------|-------|
| <b>Ply Rating</b>                 | 6     |
| <b>TKPH</b>                       | 1     |
| <b>Section Width (mm)</b>         | 315   |
| <b>Overall Diameter (mm)</b>      | 850   |
| <b>Static Loaded Radius (mm)</b>  | 385   |
| <b>Rolling Circumference (mm)</b> | 2550  |
| <b>Rim Rec</b>                    | 10 LB |

## Load capacity (Kg)

|                   |             |
|-------------------|-------------|
| <b>km/h / bar</b> | <b>2.00</b> |
| <b>10</b>         | <b>1410</b> |

Printed on 22/07/2024 11:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..