

TR 135 - Technical Specifications



Description

TR 135 is best suitable for tractors in soil tillage applications. Its reinforced casing and the special cut-and-chip resistance compound provide an extended tire life-cycle. Traction, self-cleaning properties and load capacity are key features which make the TR 135 tire the ideal partner even on the most difficult ground conditions.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Tractor
Industrial: Trailer

Version	STANDARD
Type	TL
Tyre Size	20.8 - 38
LI/SS	156 A6

Dimensions International Standard

Ply Rating	12
Section Width (mm)	530
Overall Diameter (mm)	1835
Static Loaded Radius (mm)	846
Rolling Circumference (mm)	5684
SRI (mm)	875
Rim Rec	W 18 L
Rim Alt	W 16 L
ECE	E4-106R-002272
TRA Code	R1

Load capacity (Kg)

km/h / bar	2.00
30	4000

Printed on 22/07/2024 11:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..