

XL GRIP (BHL) - Technical Specifications



Description

XL GRIP has been specially designed for backhoe loaders that are employed in heavy-duty operations in excavation, dozing and loading applications. The non-directional tread pattern provides best traction and stability. The special tread compound results in excellent cut and chip resistance and an extended tread life.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Backhoe Loader

Version	INDUSTRIAL
Type	TT
Tyre Size	12.00 - 24

Dimensions US Standard

Usa code	94046270
Ply Rating	20
Overall Width (inch)	12.6
Overall Diameter (inch)	49.2
Static Loaded Radius (inch)	23
Rolling Circumference (inch)	146.1
Rim Rec	8.5
Rim Alt	8.0

Load capacity (lbs)

mph / psi	120	120
5	15210	-
25	-	10650

Printed on 30/06/2024 18:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..