

## XL GRIP (L3) - Technical Specifications



### Description

XL GRIP (E-3/L-3) is a wide-base bias-ply tire for loaders designed to minimize cuts and punctures in heavy-duty loading applications. It provides exceptional traction as well as an extended tire life.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industrial: Loader

OTR: Dozer • Loader

Version	STANDARD
Type	TL
Tyre Size	15.5 - 25

## Dimensions US Standard

Usa code	94051182
Ply Rating	12
Overall Width (inch)	15.8
Overall Diameter (inch)	50.6
Static Loaded Radius (inch)	22.6
Rolling Circumference (inch)	148.3
Rim Rec	12.00/1.3
Rim Alt	12.00/1.3 (DC)
TRA Code	E3/L3

## Load capacity (lbs)

mph / psi	36	58
30	7160	-
5	-	12350

Printed on 30/06/2024 17:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..