



XL GRIP PLUS - Data Sheet

Description

XL GRIP PLUS (L-4) has been specially designed for loaders. Its deep tread provides high cut and puncture resistance as well as an extended tire life-cycle. XL GRIP PLUS is particularly suitable for heavy-duty service.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Dozer • Loader



SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
26.5 - 25	STANDARD	L4	28	22.00/3.0		690	1775	815	5253	TL
26.5 - 25	STANDARD	L4	32	22.00/3.0		690	1775	815	5253	TL
29.5 - 25	STANDARD	L4	28	25.00/3.5		760	1915	876	5709	TL
29.5 - 25	STANDARD	L4	32	25.00/3.5		760	1915	876	5709	TL
29.5 - 25	STANDARD	L4	36	25.00/3.5		760	1915	876	5709	TL
35/65 - 33	STANDARD	L4	42	28.00/3.5		900	2080	0	0	TL

Printed on 30/06/2024 21:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..