

## AGRIMAX RT 765 - Technical Specifications



### Description

AGRIMAX RT 765, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction and comfort on all surfaces at any time. This tire provides great self-cleaning properties and reduced soil compaction. Two sizes are available with steel-belted technology.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	280/70 R 18
LI/SS	114 A8/B

## Dimensions International Standard

Section Width (mm)	275
Overall Diameter (mm)	849
Static Loaded Radius (mm)	381
Rolling Circumference (mm)	2547
SRI (mm)	400
Rim Rec	W 9
Rim Alt	W 8 ; W 10
ECE	E4-106R-000635
TRA Code	R1W

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	555	640	735	830	925	1015	1100	1180
40	555	640	735	830	925	1015	1100	1180
30	595	685	785	890	990	1090	1180	1265
10 LT	745	860	985	1110	1240	1365	1475	1585
10 HT	595	685	785	890	990	1090	1180	1265

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/5/2025 5:01 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..