

AGRIMAX RT 855 - Technical Specifications



Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	320/85 R 32 (12.4 R 32)
LI/SS	126 A8/B

Dimensions International Standard

Section Width (mm)	329
Overall Diameter (mm)	1357
Static Loaded Radius (mm)	621
Rolling Circumference (mm)	4081
SRI (mm)	650
Rim Rec	W 11
Rim Alt	W 9 ; W 10
ECE	E4-106R-000758
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	935	1090	1245	1395	1550	1700
40	935	1090	1245	1395	1550	1700
30	1005	1165	1330	1495	1660	1820
10 LT	1255	1460	1665	1870	2075	2280
10 HT	1005	1165	1330	1495	1660	1820

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/12/2025 5:44 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..