

## AGRIMAX RT 855 - Technical Specifications



### Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	340/85 R 36 (13.6 R 36)
LI/SS	132 A8/B

## Dimensions US Standard

Usa code	94021642
Section Width (inch)	13.9
Overall Diameter (inch)	58.7
Static Loaded Radius (inch)	27.1
Rolling Circumference (inch)	177.4
Rim Rec	W 12
Rim Alt	W 11
ECE	E4-106R-000763
TRA Code	R1W

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23
30	2420	2820	3220	3620	4010	4410
25	2420	2820	3220	3620	4010	4410
20	2600	3020	3450	3870	4300	4720
5 LT	3250	3790	4320	4850	5380	5910
5 HT	2600	3020	3450	3870	4300	4720

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/12/2025 5:49 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..