

AGRIMAX RT 855 - Technical Specifications



Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	420/85 R 24 (16.9 R 24)
LI/SS	137 A8/B

Dimensions US Standard

Usa code	94029556
Section Width (inch)	17.7
Overall Diameter (inch)	52.1
Static Loaded Radius (inch)	22.9
Rolling Circumference (inch)	153.5
Rim Rec	W 15 L
Rim Alt	W 14 L ; W 13
ECE	E4-106R-000595
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
30	2790	3250	3700	4170	4620	5070
25	2790	3250	3700	4170	4620	5070
20	3000	3480	3970	4460	4950	5430
5 LT	3750	4350	4970	5580	6190	6800
5 HT	3000	3480	3970	4460	4950	5430

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/12/2025 5:47 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..