

AGRIMAX RT 955 - Technical Specifications



Description

AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying and vineyards. The special tread design with a rounded shoulder provides excellent traction performance, stability and self-cleaning properties. Thanks to its strong casing, AGRIMAX RT 955 has a high load capacity.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	270/95 R 36 (11.2 R 36)
LI/SS	139 A8/B

Dimensions International Standard

Section Width (mm)	275
Overall Diameter (mm)	1428
Static Loaded Radius (mm)	665
Rolling Circumference (mm)	4335
SRI (mm)	675
Rim Rec	W 9
Rim Alt	W 8 ; W 10
ECE	E4-106R-000659
TRA Code	R1

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
50	950	1240	1510	1655	1750	1920	2090	2260	2430	-
40	950	1240	1510	1655	1750	1920	2090	2260	2430	-
30	1020	1330	1620	1775	1880	2060	2245	2425	2605	-
10	1130	1425	1750	2080	2410	2480	2775	3065	3355	3645

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/4/2025 11:06 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..