

AGRIMAX TURF RT 333 - Technical Specifications



Description

AGRIMAX TURF RT 333 (R-3+) is a radial tire designed for small tractors in gardening, vineyards and orchards applications. Its rounded shoulder design provides low soil compaction and makes it extremely delicate on the ground. Its unique extra-deep tread (R-3+) and the special design with directional blocks stand for excellent traction both in the field and on the road, and an extended tire life cycle. AGRIMAX TURF RT 333 (R-3+) ensures great selfcleaning properties and thanks to its low rolling resistance, allows for significant fuel saving.

UM

International Standard

Construction



₩ RADIAL

Machinery

Agriculture: Orchard Harvester • Small Tractor • Vineyard Harvester

Version	STANDARD
Туре	TL
Tyre Size	200/65 R16
LI/SS	94 A8/B

Dimensions International Standard

Section Width (mm)	202
Overall Diameter (mm)	666
Static Loaded Radius (mm)	309
Rolling Circumference (mm)	2000
SRI (mm)	320
Rim Rec	W6
ECE	E11-106R-007678

Load capacity (Kg)

km/h / bar	0.6	8.0	1.0	1.2	1.4	1.6	2.0	2.4
50	315	370	425	470	520	560	625	670
40	315	370	425	470	520	560	625	670
30	340	400	455	505	555	600	670	720
10 LT	425	495	570	630	695	750	840	900
10 HT	340	400	455	505	555	600	670	720

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/5/2025 1:56 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..