

AGRIMAX TURF RT 333 - Technical Specifications



Description

AGRIMAX TURF RT 333 (R-3+) is a radial tire designed for small tractors in gardening, vineyards and orchards applications. Its rounded shoulder design provides low soil compaction and makes it extremely delicate on the ground. Its unique extra-deep tread (R-3+) and the special design with directional blocks stand for excellent traction both in the field and on the road, and an extended tire life cycle. AGRIMAX TURF RT 333 (R-3+) ensures great selfcleaning properties and thanks to its low rolling resistance, allows for significant fuel saving.

UM

International Standard

Construction



Machinery

Agriculture: Orchard Harvester • Small Tractor • Vineyard Harvester

Version	STANDARD
Туре	TL
Tyre Size	215/65 R 14
II/SS	90 A8 / 90 B

Dimensions International Standard

Section Width (mm)	220
Overall Diameter (mm)	630
Static Loaded Radius (mm)	290
Rolling Circumference (mm)	1906
SRI (mm)	310
Rim Rec	W 7
Rim Alt	W 6
ECE	E11-106R-0010331

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0
50	280	325	375	415	465	510	600
40	280	325	375	415	465	510	600
30	300	350	400	450	500	550	645
10 LT	375	435	500	560	620	685	805
10 HT	300	350	400	450	500	550	645

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/5/2025 1:55 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..