

# AGRIMAX V-FLECTO - Technical Specifications



## Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the innovative VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.

## UM

US Standard

## Construction

 RADIAL

## Machinery

Agriculture: High-Power Tractor

Version	STANDARD
Type	TL
Tyre Size	VF 710/55 R 34
LI/SS	170 D

## Dimensions US Standard

Usa code	94513376
Section Width (inch)	27.9
Overall Diameter (inch)	65.3
Static Loaded Radius (inch)	28.6
Rolling Circumference (inch)	193.3
Rim Rec	DW 25 B
Rim Alt	DW 27 B
Narrow Rim option	DW 23 B
ECE	E11-106R-0010831
TRA Code	R1W

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29
45	5900	6860	7940	8910	9870	10820	12040
from 40 to 25	6480	7540	8730	9790	10850	11900	13230
20	6600	7680	8900	9980	11060	12140	13490
12	6730	7840	9070	10170	11280	12380	13760
5	7120	8290	9600	10760	11930	13090	14550
*Upto 5 Cyc with front loader	9070	10550	12210	13700	15180	16670	18520
5 HT	6600	7680	8900	9980	11060	12140	13490

\* \*For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/5/2025 2:55 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..