



## ARROW - Data Sheet



### Description

ARROW is suitable for transport applications with trailers. It is a road-oriented tire that provides a better mileage and a longer service life. ARROW has a high load capacity also at high speeds. An HD version made of a special compound is also available for users that require advanced performance.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Trailer

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	Type	ECE
6.50 - 14	STANDARD	10	4.5 J		175	695	TT	E4-54R-0024093
6.50 - 14 LT	HD	10	4.5 J		175	695	TT	
7.50 - 16	STANDARD	12	6.00 G	5.50 F	216	825	TT	
7.50 - 16	STANDARD	14	6.00 G	5.50 F	216	825	TT	
7.50 - 16	STANDARD	16	6.00 G	5.50 F	216	825	TT	
10.00 - 20	STANDARD	16	7.5	7.0 ; 8.0	286	1075	TT	
9.00 - 20	STANDARD	14	7.0	6.5 ; 7.5	270	1040	TT	
9.00 - 20	STANDARD	16	7.0	6.5 ; 7.5	270	1040	TT	
9.00 - 20	TRACTOR TRAILER	16	7.0	6.5 ; 7.5	270	1040	TT	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/12/2025 4:33 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..